

LeakMaster

CUTTING EDGE LEAK TESTING TECHNOLOGY

STEALTH



The LeakMaster Stealth is a cost effective, compact leak tester that is extremely accurate and user friendly. At only 4.5" wide the Stealth is well suited for a wide range of installations from lab environments and medical clean room applications to abusive environments. The Stealth is configurable for pressure decay, vacuum decay, differential pressure or occlusion testing. Manufactured to operate as a standalone instrument with or without the use of the optional touch screen pendant. Stealth can also be controlled through slave mode via customer PLC.

POWER. PERFORMANCE. *SPEED.*

SUPERIOR PERFORMANCE & FEATURES

COMPACT SIZE & PRICE!



SHOWN WITH OPTIONAL TOUCH SCREEN PENDANT

NEW AND IMPROVED **EtherNet/IP™** FEATURING “SLAVE MODE”. 64 BIT PROCESSOR FOR SPEED & REPEATABILITY. 24 BIT DIGITAL PRESSURE TRANSDUCER FOR EXTREME RESOLUTION. EXTREMELY COMPACT DESIGN



RUN SCREEN

- The touchscreen display makes leak testing effortless.
- All pass/fail and in-process information are clearly displayed for easy viewing.



SET UP SCREEN

- The easy to understand layout reduces set-up time, builds confidence, and eliminates confusion.
- The intuitive design gives unparalleled control, without multiple set-up screens.
- All leak timers and limits are clearly presented in their proper order.



RESULTS SCREEN

- Built-in data collection with auto save for proven, effective data collection; without hassle.
- The information is saved as a CSV file for viewing in Microsoft Excel or other text viewers.

TECHNICAL SPECIFICATIONS

FEATURE	STANDARD	OPTIONAL
PROGRAMS PER CHANNEL	10	
# OF CHANNELS	1	
TEST TYPE	PRESSURE OR VACUUM	DIFFERENTIAL
INPUTS		(16) 24VDC PNP
OUTPUTS		(16) 24VDC PNP
COMMUNICATIONS	ETHERNET IP®	DIGITAL IO
DATA COLLECTION	USB FLASH, NETWORK	
PRESSURE REGULATOR	CUSTOMER SUPPLIED	
TRANSDUCER	0-150 PSI, 0-60 PSI, 0-15 PSIG, 0-15 PSIA	0-1.45 PSID

